

# FASTORQ 600 Series Power Units

## MODEL 606A

**6K high-speed hydraulic torque wrench pump suited for demanding turnaround and shutdown maintenance operations.**

### Features:

- 7 HP Air Motor
- Positive displacement reciprocating fluid end
- 6,000 psi Operation
- Flow Data: 1,155 in<sup>3</sup>/min. @ 0 psi; 487 in<sup>3</sup>/min. @ 3,000 psi; & 122 in<sup>3</sup>/min. @ 6,000 psi
- Precision Valve for torque and pressure control adjustment
- Glycerin filled easy to read pressure gauge
- Air Inlet filter, regulator, lubricator assembly
- 3-gallon hydraulic reservoir
- Spin-On 10-micron oil filter
- Oil Gauge
- Temperature Gauge
- Self Cooled
- Low maintenance
- Rugged
- Hand held 2-button remote control pendant with 25' color-coded lines
- All mounted on a 2-wheel mobile hand truck for maximum portability
- Optionally available mounted in a ridged steel frame

### Safety Features:

- If the button of the remote control is released or the remote control is dropped, the pump and torque wrench will come to an immediate stop
- Equipped with twin air exhaust valves

### Air Requirement:

- Requires 150 cfm air volume @ 100 psi for optimum performance



**Model 606A High Speed Pump**

